

SRWOOD

PRODUCT #850D

SPECIFICATIONS

Dura-Bull

CraftWood's Dura-Bull consists of stress-relieved wood that is bonded using a specific heat and pressure to a specifically formulated poly resin impregnated paper.

This product is designed to work with the new water-based adhesives. Resistant to shrinkage, ripping and water.

CHARACTERISTICS

REQUIREMENTS

VENEER CUT

Various—depending on species. Includes Flat Cut, Rift Cut and Ribbon Cut.

VENEER THICKNESS

Varies from 1/50" to 1/64" on most species.

BACKER

Poly resin impregnated kraft paper, back sanded to facilitate bonding. Backer thickness is .020.

TOTAL THICKNESS

Varies between .032 and .039 depending on species and amount of sanding to the veneer.

TYPES OF MATCH

All sheets are book matched unless otherwise specified and can be sequence matched from sheet to sheet if requested.

SHEET SIZES

4' X 8' and 4' X 10' are standard size, available in most species on special order sizes from 3' X 8' - 5' X 12' available.

INSTALLATION

For interior use only. To be bonded to suitable substrates such as plywood, particleboard or flake board this product may also be used to resurface metal and wood doors. Use a good quality contact adhesive manufacturer's recommended techniques. Light sanding with 120 grit sandpaper after post-forming will smooth out open grains such as Oak and Ash.

FINISHING

Any good quality polyurethane stain and finishing system can be employed following the coating manufacturer's instructions.